

What is Drive Away?

DRIVE AWAY is a unique solvent-based cleaner which dissolves oil and grease spots from both porous and sealed concrete surfaces.

Key Benefits

- ✓ DRIVE AWAY attacks oil and grease and dissolves spots from concrete.
- ✓ DRIVE AWAY emulsifies with water allowing oil and grease to be simply hosed away.

How Does It Work?

DRIVE AWAY is a powerful, hydrocarbon based cleaner which readily attacks and dissolves grease and oil. The detergent ingredients then emulsify the oil and enable it to be washed away with water or steam. DRIVE AWAY actively removes oil and grease from engines, machinery, tools, concrete parking bays, driveways and workshop floors.

Technical Data

Composition

DRIVE AWAY is a blend of detergent surfactants and hydrocarbon solvents.

Properties



COLOUR – Transparent brown liquid
 ODOUR – Kerosene-type odour
 SOLUBILITY – Self-emulsifies in water
 FLAMMABILITY – DRIVE AWAY is FLAMMABLE.
 Do not use near ignition sources such as cigarettes, fires, heaters, stoves, TV's, computers, welders, etc. Open a window for good ventilation.

Dangerous Goods Classification

DRIVE AWAY is a Class 3 flammable liquid.

U.N. No: 1993	CLASS: 3
PACK GRP: III	HAZCHEM: 3[Y]

Environmental Care



DRIVE AWAY conforms with all statutory environmental requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. DRIVE AWAY is phosphate-free. DRIVE AWAY containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

Application

Caution

DRIVE AWAY is flammable. Avoid sources of ignition. Avoid skin contact and avoid inhaling vapours.

- Floors: Please follow these directions carefully to get the best results.
 - Dilute DRIVE AWAY to 1 in 4 (for each 1L of DRIVE AWAY add 3L of cold water).
 - If the floor is porous, like unsealed concrete, wet the area around the stains with clean water. This will prevent the oil and degreaser from spreading or soaking further into the floor.
 - Pour the DRIVE AWAY solution onto the oil stains and leave in place for at least 7 minutes. Brushing is not essential but will speed up process.
 - Rinse off or scrub with water and vacuum or mop up the solution for disposal to the sewer.
- Car parts may be soaked in DRIVE AWAY (neat or diluted up to 1 in 10) and hosed down with hot water for complete removal of dirty oily films and grease.

First Aid

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone 131 126 in Australia). If swallowed, do NOT induce vomiting. Give a glass of water. Refer to the DRIVEAWAY Safety Data Sheet for more information.

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.