

Product Data Sheet

Product Code: GRAF

Issued: February 25, 2011

What is Graffiti Remover?

GRAFFITI REMOVER is an effective, low odour product that dissolves ink and paint graffiti from surfaces subject to graffiti.

How Does It Work?

GRAFFITI REMOVER is a powerful solvent-type paint and ink removal agent. It is water-emulsifiable so it can be rinsed away effectively with water. It is a low odour liquid with outstanding performance and it is a thickened liquid so it will "cling" to vertical surfaces. GRAFFITI REMOVER will not leave unwanted chemical odours after being used. It is not classified as Dangerous Goods.

For Use On...

GRAFFITI REMOVER quickly and thoroughly dissolves aerosol paint, felt-tipped pen ink, ballpoint pen ink and other graffiti from metal, fibreglass, concrete, brickwork and even carpeted surfaces. It is ideal for use in railway carriages, on walls and brickwork, and all other surfaces subjected to graffiti.

Caution

Use caution before applying GRAFFITI REMOVER to soft vinyl or plastic. It is advisable to pre-test the product on unknown or sensitive surfaces to ensure no damage will occur. Avoid spilling the product on paintwork, shoes and furniture. Wear solvent-resistant gloves (nitrile or neoprene) to prevent skin contact. Do not leave the product lying around after use. Also, avoid using food containers for storing the product.

Technical Data

Properties

COLOUR – Transparent colourless liquid

ODOUR – Low odour

pH = Not applicable

VISCOSITY – "Thick" liquid

Environmental Care



GRAFFITI REMOVER conforms with all statutory environmental requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. GRAFFITI REMOVER containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

Application

- Graffiti is easiest to remove when it is fresh.
- GRAFFITI REMOVER is not suitable for use on painted surfaces because it will strip the paint. To remove graffiti from painted walls, use DLX.
- **Metal, Fibreglass, Tiles, Glass**
 1. Brush GRAFFITI REMOVER onto the graffiti. Apply a thick uniform film.
 2. Scrub for a minute with a brush to assist penetration. Smooth over then leave to work for 5 minutes.
 3. Scrub the graffiti with a brush or a nylon scourer.
 4. Wipe the graffiti off with a rag, or rinse off with a hose.
 5. If any graffiti is left, repeat steps 1 to 4.
 6. Wipe over all areas with clean water.
- **Concrete or Brick**
 1. Use a stiff nylon or wire brush.
 2. Follow steps 1 to 4 above.
 3. Brush over all treated areas then rinse with clean water.

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.