

Product Data Sheet

Product Code: JE

Issued: February 25, 2011

What is Jetsol?

JETSOL is a powerful, grease-cutting cleaner which attacks and removes marks and soilage from hard surfaces.

Key Benefits

- ✓ Excellent remover of hard-to-shift soils.
- ✓ Even removes ink, glue and grease marks.
- ✓ Non-flammable.

How Does It Work?

JETSOL is a powerful grease-cutting cleaner which attacks and dissolves dirt, ink, grease, oil, fat, crayon, price sticker adhesive, and a wide range of soils from washable hard surfaces.

For Use On...

JETSOL will remove all soils including dirt, food spills, greasy oil films, fat, carbon and smoke deposits, bathroom build-ups, lipstick etc.

JETSOL will clean all washable hard surfaces – walls, stoves, laminex, glass, shower recesses, paintwork, venetian blinds, porcelain, stainless steel, chrome etc. It is great for school desks and bank counters where ink stains are found.

Technical Data

Composition

JETSOL is a concentrated water-based cleaner and stain remover. It contains powerful surfactants and water-soluble solvents for rapid attack of soilage and stains.

Properties



COLOUR – Transparent, colourless liquid
ODOUR – Mild solvent odour
pH = 10.5
FOAM – Low foaming

Environmental Care

JETSOL conforms with all statutory environmental requirements.



It is based on safe ingredients selected to perform efficiently so there is no waste or damage. JETSOL is non-flammable and biodegradable. JETSOL containers will be cleaned and reused if returned to Agar Cleaning Systems Pty Ltd., significantly reducing plastic usage and waste. They can also be recycled.

Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements".

First Certified: 30 April 1996

SAI Certificate No.: QEC7358

Application

1. Apply JETSOL solution by spray, cloth or mop, depending on the type of surface to be cleaned.
2. Make up the correct dilution of JETSOL with water (see below).
3. Mop or spray the JETSOL solution onto the surface and allow it to penetrate the stains.
4. Wipe with a clean cloth or mop to remove the marks and soilage.

➤ Dilution Rates:

Light Soilage: Dilute 1 part of JETSOL with 10 parts of water.

Medium Soilage: Dilute 1 part of JETSOL with 4 parts of water.

Heavy Soilage and Stains: Use neat JETSOL.

- Avoid prolonged contact between JETSOL and uncoated aluminium and water-based paints.

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.