

Product Data Sheet

Product Code: BO

Issued: September 4, 2001

Environment



ULTRASTRIP conforms with all statutory environment requirements. It is based on safe ingredients selected to perform efficiently so there is no waste or damage. ULTRASTRIP is non-flammable, phosphate free and biodegradable. Containers are recycled wherever possible.

Main Benefits

- ✓ Odourless
- ✓ Easy to rinse
- ✓ Complete stripping action, even on stubborn coatings
- ✓ Rips through old polish and heavy build-ups
- ✓ Floors are not slippery to walk on when ULTRASTRIP is in use

Product Use

ULTRASTRIP is a low foaming stripper with a free rinsing action that leaves floors stripped and ready for recoating. It has a low concentration of volatile ingredients so it is practically odourless to work with. It will not affect metal, vinyl tile or wood surfaces but must be diluted for stripping rubber floors. It should be well diluted and used cautiously on sheet vinyl floors.

Action

ULTRASTRIP gives fast and complete attack of sealer and wax films. The speed and depth of its reaction decrease the need for machining, thereby saving time.

Technical Data

Properties



COLOUR – Transparent, colourless liquid
ODOUR – Mild odour
pH = 11 ± 0.5
FOAM – Low foaming

Composition

ULTRASTRIP is a super-concentrated stripper that has a powerful formula for ripping through old films and build-ups of hardened floor sealer allowing all traces to be rinsed away easily.

Application

- Dilute 1 part of ULTRASTRIP with from 10 to 20 parts of cold water. For severe polish build-ups higher concentrations up to 1 in 3 ULTRASTRIP may be used, but for rubber or sheet vinyl floors it MUST be diluted to at least 1 in 20 with water.
- Mop ULTRASTRIP solution generously over the floor and allow 10 to 15 minutes to activate. Keep the floor wet with solution; don't let it dry out (apply more if necessary).
- Scrub floor with a black pad under a slow machine, spending more time along the edges where the sealer will be thickest.
- Mop up solution and rinse floor with clean hot water.
- Floors that are porous should be flood-rinsed i.e., should be completely covered with clean hot water and then wet-vacuumed or mopped up. This is needed to remove the stripper from all of the pores in the floor.

(See related Task Sheet – FC05)

Agar Cleaning Systems maintains Material Safety Data Sheets (MSDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective MSDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.



MELBOURNE
Agar Cleaning Systems Pty. Ltd.
12-14 Cope Street
PRESTON VIC 3072
Ph: (03) 9480 3000

ADELAIDE
Agar Cleaning Systems Pty. Ltd.
Unit 2, 59-63 Mooringe Ave
PLYMPTON SA 5038
Ph: (08) 8293 2020

BRISBANE
Agar Cleaning Supplies
Unit 1, 3 Johnstone Rd
BRENDALD QLD 4500
Ph: (07) 3205 7244

SYDNEY
Agar Cleaning Systems Pty. Ltd.
Unit 4, 25 George Street
HOMEBUSH NSW 2140
Ph: (02) 9743 6020

PERTH
Briskleen Supplies
Unit 5, 7 Agett Road
MALAGA WA 6062
Ph: (08) 9249 4566